

Model Number	Exterior Dimensions (WxDxH)	Interior Dimensions (WxDxH)	Cubic Feet	Standard Door Sizes	Refrigeration HP Sizes (single stage or cascade)
WIT-316	81.5"x104.5"x104.5"	73.5"x77.5"x96"	316	36" x 77" 48" x 77"	5.0, 7.5, 10.0, 15.0, 25.0, 30.0
WIT-366	93"x104.5"x104.5"	85"x77.5"x96"	366	36" x 77" 48" x 77"	5.0, 7.5, 10.0, 15.0, 25.0, 30.0
WIT-477	104.5"x116"x104.5"	96.5"x89"x96"	477	36" x 77" 48" x 77" 72" x 77"	5.0, 7.5, 10.0, 15.0, 25.0, 30.0
WIT-539	104.5"x127.5"x104.5"	96.5"x100.5"x96"	539	36" x 77" 48" x 77" 72" x 77"	5.0, 7.5, 10.0, 15.0, 25.0, 30.0
WIT-603	116"x127.5"x104.5"	108"x100.5"x96"	603	36" x 77" 48" x 77" 72" x 77"	5.0, 7.5, 10.0, 15.0, 25.0, 30.0
WIT-744	127.5"x139"x104.5"	119.5"x112"x96"	744	36" x 77" 48" x 77" 72" x 77"	5.0, 7.5, 10.0, 15.0, 25.0, 30.0
WIT-820	127.5"x150.5"x104.5"	119.5"x123.5"x96"	820	36" x 77" 48" x 77" 72" x 77"	5.0, 7.5, 10.0, 15.0, 25.0, 30.0
WIT-983	139"x162"x104.5"	131"x135"x96"	983	36" x 77" 48" x 77" 72" x 77"	5.0, 7.5, 10.0, 15.0, 25.0, 30.0
WIT-1069	150.5"x162"x104.5"	142.5"x135"x96"	1069	36" x 77" 48" x 77" 72" x 77"	5.0, 7.5, 10.0, 15.0, 25.0, 30.0
WIT-1160	150.5"x173.5"x104.5"	142.5"x146.5"x96"	1160	36" x 77" 48" x 77" 72" x 77"	5.0, 7.5, 10.0, 15.0, 25.0, 30.0
WIT-1351	162"x185"x104.5"	154"x158"x96"	1351	36" x 77" 48" x 77" 72" x 77"	5.0, 7.5, 10.0, 15.0, 25.0, 30.0

IMPORTANT NOTES:

Single stage Refrigeration Temp range: -35°C to 85°C

Cascade Refrigeration Temp range: -68°C to 85°C

Refrigeration Horsepower (HP) sizes shown are available in air-cooled or water-cooled configuration

Chambers are available as temperature only or temp-humidity configuration

For units with Humidity, Humidity Range: 20% to 95% over the temperature range of 20°C to 70°C, limited by a 5°C dew point. Optional dry bulb temperature range to 85°C with RH control.

Voltage Configuration Available: 208V-3Ph-60Hz / 240V-3Ph-60Hz / 460V-3Ph-60Hz - Please consult factory for 50Hz applications.

Door Ramp available as an Option